



**MODEL LP 550 "PUP"
MEDIUM DUTY TURNTABLE
STRETCH WRAP SYSTEM GENERAL SPECIFICATIONS**

PRODUCTION SPEED

- 1-15 loads per hour

NOTE: Process rates will vary with load size; number of wraps & forklift load/unload time

LOAD CAPACITY

- Maximum load weight: 3,000# dynamic – 8,000# static
- Maximum load size: 48" W x 48" L x 75" H (68" Max. load diagonal)

NOTE: Maximum load size shown is the largest load PUP will wrap – no exceptions

TURNTABLE

- 57" Diameter 5/16" thick laser-cut steel plate
 - 18 point turntable support system
 - Turntable height 2-1/4" from floor
 - ANSI # 50 Direct Chain Drive c/w chain tensioner
 - 1 - 9 RPM rotational speed c/w soft start acceleration
 - 1/3 HP VDC variable speed gear-motor
 - Safety surround ring encloses turntable
-

**FILM CARRIAGE
ELEVATOR**

- 1/8 HP VDC variable speed gear-motor
 - Direct flat belt drive system
 - 4 point "V" wheel carriage guidance system with side thrust rollers
-

CONTROL FEATURES

- Simple to operate
- Power On / Emergency Stop Button
- Turntable Jog / Run Switch
- Film Carriage Lower / Raise Switch
- Film Carriage Variable Speed Control
- Turntable Variable Speed Control
- Non-proprietary UL/CSA approved components

**STRUCTURAL
FEATURES**

- Formed steel base construction
- Formed steel metal tower
- Forklift truck portable base design – pick-up angles included

**ELECTRICAL INPUT
REQUIREMENTS**

- 115 Volts 1 Phase 60 Hz 10 Amps
-