



The Model **USA-2024-SB** features include; machine base, legs, columns and Top Tape head housing are manufactured from 10 and 12 gauge steel, formed and welded for structural strength. Double columns provide maximum carton processing stability. 2" tall drive belts are permanently anti-static, finger spliced and manufactured from EPTP for wear resistance, pre-loaded on assembly, belts adjust automatically. Two 1/3rd H.P., 115 volt, 60 HZ, Totally Enclosed Fan Cooled single phase parallel shaft gear motors each develop 90 in.lb. torque. Belt speed is 82 feet/minute. There are 2 motor starters with overload protection.

To facilitate fast, accurate carton size changeover, the Top Tape Head Assembly contains twin linear bearings and is counter-balanced with twin constant force flat springs per column. The top tape head assembly provides ¾" "floating" capabilities for compressible overfills. Ball bearing conveyor rollers provide maximum carrying capacity with minimal friction.

All non-painted surfaces are plated or anodized for corrosion resistance.

Intertape case sealers do not require lubrication.

Each **USA-2024-SB** Carton Sealer has two high performance HSD[®] 2000-ET II pressure sensitive tape dispensing heads featuring; large diameter stainless steel shafts and Glycodur[®] bearings, smart core mandrels provide maximum tape processing control, tool steel cut-off blades are hardened and ground to Rockwell C 60-62, moulded urethane tape wipe down rollers provide exceptional toughness and wear resistance. A Torrington one way clutch bearing controls tape application and ensures tape length accuracy. A flipper style blade guard with oiler pad provides maximum safety while lubricating the cut off blade with every processing cycle. A tape wipe down brush applies tape evenly to corrugated cases. True side threading feature simplifies tape roll replacement. High tensile S.H.C.S. fasteners will not loosen during high volume processing operation.

HSD[®] 2000 ET II Tape Heads never require lubrication.



Price Includes:

- 2" Tall Drive Bases With 1/3rd Hp Gearmotors
- Telescopic Leg Extensions To Adjust From 24" To 30" Bed Height
- 2" Wide HSD 2000-ET II Taping Heads
- Removable And Interchangeable Taping Heads
- Floating Top Tape Head Assembly
- Reversible Controls From Left To Right Side
- Top Squeezers
- Infeed Box Guides
- Single Locking Device Secures Top Tape Head Assembly To Both Column

PRICE

FOB Tampa, Fl., FREIGHT COLLECT

\$5875.00

Options:

A. Set of four casters (part no. UM841)	\$205.00
B. Infeed / Exit table (part no. UM894)	\$345.00
C. Three Flap Folder (part no. UM869)	\$335.00
D. Spare 2" HSD 2000-ET II Tape Head	\$1195.00
E. Upgrade to 3" Wide Taping Heads	\$375.00

Payment Terms:

Net 30 Days With approved credit.

Tax:

Plus Applicable Sales, Use, Privilege Or Excise Taxes And Federal, State Or Local, If Any

F.O.B.:

Source

Delivery:

2-3 Weeks From Receipt Of A Firm Purchase Order

Warranty:

One Year; Wear Parts 90 Days

Order Acceptance:

Subject To Qualification Of RSC Cartons



The Intertape Polymer Group may require an ample supply of production boxes plus product for testing prior to shipment

This quotation is valid for 30 days from above date.